

## PLATE DEVELOPERS AND REPLENISHERS FOR ANALOGUE PLATES

CONCENTRATED DEVELOPER FOR ANALOGUE POSITIVE PLATES.

### PROPERTIES

- ▶ Weakly buffered. Allows the elimination of film edges without affecting dot reproduction.
- ▶ Its formulation characteristics make it easily miscible with all water types.
- ▶ Reduces calcium residues in the developer bath.

### APPLICATION

- ▶ Applicable for all positive plate lines, it is recommended for:
  - ▶ Hand development.
  - ▶ Development in processors with immersion and spray systems.
  - ▶ Tray or dish development.

### METHOD OF USE

- |                                    |                         |             |
|------------------------------------|-------------------------|-------------|
| ▶ Advised dilution:                | DEVELOPER               | REPLENISHER |
| ▶ Plate line <b>TOP F100</b>       | 1+8                     | 1+6         |
| ▶ Recommended working temperature: |                         |             |
| ▶ Hand:                            | 20-22°C                 |             |
| ▶ Processor:                       | 24 °C ± 1 °C            |             |
| ▶ Development time:                |                         |             |
| ▶ Hand:                            | 45-60 seconds           |             |
| ▶ Processor:                       | 30 ± 5 seconds          |             |
| ▶ Replenishment rate:              | 70-90 ml/m <sup>2</sup> |             |

### CONSIDERATIONS

- ▶ Adequate replenishment keeps filters and circulation systems clean prolonging the life of the bath.
- ▶ Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor.
- ▶ Clean using **PROCESSOR CLEANER PC-520** and **PROCESSOR CLEANER PC-600**.

### PACKAGING

- ▶ 10 litres.
- ▶ 25 litres.
- ▶ 200 litres (with dosing device).

Note:  
The results obtained may vary depending if the conditions of use are outside of our recommended values.